



Barracuda III Model 6096 Fish Cleaning Station



Standard Features:

- Heavy-duty, dual-shaft waste grinder
- Exclusive dual 8½" inlet protects both your patrons and the grinder
- ¾" Sanalite cutting boards that slope to central drainage basin
- Side-mounted, 60" x 19" x 34" high ADA-compliant cutting table
- Two Start/Stop control stations
- Adjustable flow, automatic basin rinse
- Four 60" side-mount spray hoses
- Four 120V GFCI convenience outlets
- Welded T304 stainless steel cabinet with adjustable leveling feet
- Lockable doors and removable front panel for maintenance access
- Shipped fully assembled

Grinder Specifications:

- 5HP/230VAC motor
- 29:1 gear ratio
- Counter-rotating, 60 RPM shafts with 26 hardened cutters
- Discharge adapter for 6" PVC pipe

Requirements:

- 30A/240VAC, 1 or 3-phase service (no add-on converter required)
- 50-60 PSI, 1 inch water supply line (2 to 10 GPM usage)

Available Options:

- Hanging, overhead spray hoses
- Hide-away, top-mount spray hoses
- Cold-weather insulation package
- Lockable winter cover

Barracuda Intelligent Control System:

- Either green button starts grinder and basin rinse.
- Adjustable timers automatically stop grinder and rinse at the same time. After a brief pause, the rinse resumes long enough to flush all wastes through your drain. Your patrons can't leave the grinder or water running!
- **1st Jam Release™** reverses and halts the grinder on initial contact with foreign object to minimize cutter damage.
- Either red button immediately stops the grinder, pressing it twice also stops basin rinse.
- Displays daily, monthly and cumulative usage.
- Housed in NEMA 4X enclosures.

August 23, 2024



www.qualitymandm.com • sales@qualitymandm.com

272 Hwy 65 North, Conway, AR 72032

501-499-6258 * 844-766-3474